

## xEPON

### EEP2592-3SC20

### 10G SFP+ SC EPON ONU

#### Features

- SFP+ Package with SC Receptacle
- Single +3.3V Power Supply
- 10.3125 Gbps / 1270nm Burst-Mode Transmitter  
with DFB laser
- 10.3125 Gbps / 1577nm High Sensitivity  
Continuous-Mode PIN-TIA Receiver
- LVTTTL Tx\_Burst, Tx\_SD, LOS
- LVTTTL Sleep Mode for Power Consumption
- Operating Case Temperature  
Standard: 0°C~+70°C  
Industrial: -40°C~+85°C
- Compliant with Class 1 FDA and IEC60825-1  
laser safety
- Compliant with SFF-8472 MSA
- Compliant with IEEE 802.3av
- Compliant with SFP+ MSA SFF-8431
- RoHS-6 compliance



#### Applications

- 10GBASE-PR-U1 application

## Ordering information

P/N	Input	Output	Burst-M ode	Fiber	Interface	Temp
EXEP2592-3SCD20	AC	AC	LVTTL	SMF	SC	Standard
EXEP2592-3SID20	AC	AC	LVTTL	SMF	SC	Industrial

Note1: Standard version


\*The product image only for reference purpose.

## Regulatory Compliance

Product Certificate	Certificate Number	Applicable Standard
TUV	R50135086	EN 60950-1:2006+A11+A1+A12+A2
		EN 60825-1:2014
		EN 60825-2:2004+A1+A2
UL	E317337	UL 60950-1
		CSA C22.2 No. 60950-1-07
EMC CE	AE 50285865 0001	EN 55022:2010
		EN 55024:2010
FCC	WTF14F0514417E	47 CFR PART 15 OCT., 2013
FDA	/	CDRH 1040.10
ROHS	/	2011/65/EU

Note2: The above certificate number updated to June 2014, because some certificate will be updated every year, such as FDA and ROHS. For the latest certification information, please check with Eoptolink.

## Functional Diagram



## Product Description

EXEP2592-3SCD20 is a transceiver for the optical network unit (ONU) of 10GEPON with 10.3125Gbps in downstream and 10.3125Gbps in upstream. EXEP2592-3SCD20 series is high performance module for single fiber communications by using 1270nm burst-mode transmitter and 1577nm continuous-mode receiver.

The transmitter section uses a DFB 1270nm laser and is a class 1 laser compliant according to International Safety Standard IEC-60825-1. The receiver section uses an integrated 1577 nm detector preamplifier (IDP) mounted in an optical header and a limiting post-amplifier IC. CML interface is used for differential inputs and outputs. LVTTTL logic control interface simplifies the interfaces to external circuitry.

## Compatibility Test

In order to ensure the product compatibility, our products will be tested on the switch before shipment. Our modules can compatible with many mainstream brand switches, such as Cisco, Juniper, Extreme, Brocade, IBM, H3C, HP, Huawei, D-Link, Mikrotik, ZTE, TP-Link...

Our test equipment: VOLKTEK MEN-4110, HP 2530-8G, CRS226-24G-25+RM, Catalyst 2960G Series, Catalyst 3850 XS 10G SFP+, Catalyst 3750-E Series, HUAWEI S5700Series, H3C S3100V2 Series, Juniper-EX4200, etc.



**Cisco Catalyst 3850**



**HUAWEI S5700**



**H3C S3100V2**



**HP J9264AR**



**Juniper EX 4200**



**Alcatal 6850E-U24X**



**Mikrotik CR5226-24G-25+RM**



**Cisco Catalyst 2960G**



**Volktek MEN-4110**

## Product Production Process

### Quality Assurance

Continuous introduction of new equipment, produced by strict standards, strict quality inspection, to guarantee the high quality standard of each product.



**Standardized  
Production Line**




**Professional  
Welding**



**Assembling**



**Aging Testing**



**Distance Testing**



**Cleaning end face**



**Product Initial Test**



**Switch Testing**



**Product Final Test**



## Packaging

ETU-Link provides two kinds of packaging, 10pcs/Tray and individual package.



Company: ETU-Link Technology Co., LTD

Address: 4th Floor, C Building, JinBoLong Industrial Park, QingQuan Road, LongHua District, Shenzhen city, GuangDong

Tel: +86-755 2328 4603

Addresses and phone number also have been listed at [www.etulinktechnology.com](http://www.etulinktechnology.com).

Please e-mail us at [sales@etulinktechnology.com](mailto:sales@etulinktechnology.com) or call us for assistance.